

For clean wheels, a good scrub is a great start. That's why DuraScrubber®, part of Belanger's complete wheel cleaning system, offers "eight feet of clean" – a full 96-inch length to ensure that even the largest wheels get scrubbed through a complete rotation.

DuraScrubber® features alternating 12" and 7" diameter crushed end tip bristles, to clean deep between wheel spokes, while also scrubbing the intricate latticework and foreground designs of today's complex OEM and aftermarket rim assemblies.


Because a wheel scrubber is called upon twice for every vehicle washed, DuraScrubber® is built to last. Featuring a frame of double-wall aluminum and oversized pivot bearings and brush spindle bearings, DuraScrubber® is engineered for extreme durability.

Available in your choice of hydraulic or electric drive, and requiring only the corresponding hydraulic or electrical connection and an air line, DuraScrubber® is easily integrated into your wash bay. This simple installation offers you a true "set and forget" wheel cleaning solution.



2212 Camplain Road
Hillsborough, NJ 08844
1-888-8FC-LIFT



Belanger Incorporated Products Specification Sheet		
	Belanger, Inc. reserves the right to revise specifications, features or designs, and to change or discontinue models at any time without notice or obligation. Prices subject to change without notice.	
	BE0039	Copyright 2012 Belanger, Inc. ©



Specifications

DuraScrubber®

REQUIREMENTS

Physical

Component Height	14 1/2"
Minimum Tunnel Width Required	14' 9"
Minimum Tunnel Length Required	15' 6" (*May be installed underneath other compatible pieces of wash equipment)

Utilities

Hydraulic Drive Option:

Electrical Requirements	(1) one 110 VAC output from Controller to air panel
Hydraulic Lines	3.5 GPM @ 1000 PSI; 1/2" supply and return lines
Pneumatic Requirements	1/4" airline @ 90 PSI minimum, 120 PSI maximum

Electric Drive Option:

Electrical Requirements	(1) one 110 VAC output from Controller to air panel
3 Phase Motor	208V, 60Hz, 3.30 amp 230V, 60Hz, 3.30 amp 460V, 60Hz, 2.00 amp
Pneumatic Requirements	1/4" airline @ 90 PSI minimum, 120 PSI maximum



*Shown with available
green powder-coated finish*



*Shown with standard
aluminum finish*