



2212 Camplain Road
Hillsborough, NJ 08844
1-888-8FC-LIFT



Mechanical Meters

Rugged and Dependable Fluid Dispense Meters



Accurate dispensing for a wide variety of vehicle or machine service applications

- Balanced, lightweight, rugged construction, and comfortable grip
- Non-resetttable totalizing register helps manage material usage
- Handles a variety of petroleum and synthetic based oils and anti-freeze
- Ideal for indoor and outdoor use

PROVEN QUALITY. LEADING TECHNOLOGY.

Mechanical Meters

Severe Duty Mechanical Meters

Maximum Flow **8 gpm** (30 lpm)
 Minimum Flow 0.28 gpm (1 lpm)
 Maximum Operating Pressure... 1,500 psi (103 bar)
 Operating Temp Range -50 - 160° F (-45 - 70° C)

Models:



SDMP8 Preset

60 Quart
 60 Liter
 60 Gallon



SDMM8 Manual

Quart 4/16
 Liter 4/16

Accessories

24V475	Quick close nozzle with flexible extension for oil
255852	Quick close nozzle with rigid extension for oil
24W641	Quick close nozzle with short rigid extension for oil
255854	Quick close nozzle with rigid extension for gear lube
255855	Quick close nozzle with rigid extension for antifreeze
24W306	Quick close nozzle with flexible extension for antifreeze
256164	Strainer filter kit

Ordering Information



Bare



Rigid

Preset Meters – SDMP8			
NPT	60 quart	24U947	24V052
	60 gallon	24U950	24V055
	60 liter	24U953	24V058
BSPT	60 quart	24U948	24V053
	60 gallon	24U951	24V056
	60 liter	24U954	24V059
BSPP	60 quart	24U949	24V054
	60 gallon	24U952	24V057
	60 liter	24U955	24V060

Built to Last

More Uptime to Increase Your Bottom Line

Graco offers a family of engineered meters, focused on delivering a long-life, reliable solution. Each model has been vigorously tested to ensure the highest performance for your demanding applications.



Built-in totalizer

Helps manage material usage

Simple, easy design

Dial and face design is easy to read and set

Impact-resistant shroud

Resists scratches and protects knob and dial from damage

Four finger trigger

Large, comfortable trigger has lock-on and push-off release

Durable cast housing

Durable aluminum body is balanced and lightweight

Common connection points

Makes installation quick and easy with NPT, BSPT, and BSPP swivels



Bare



Rigid



Flexible



Gear Lube

Manual Meters – SDMM8					
NPT	4/16 liter	24U956	24V046	24V043	24V049
	4/16 quart	24U959	24V037	24V034	24V040
BSPT	4/16 liter	24U957	24V047	24V044	24V050
	4/16 quart	24U960	24V038	24V035	24V041
BSPP	4/16 liter	24U958	24V048	24V045	24V051
	4/16 quart	24U961	24V039	24V036	24V042

©2014 Graco Inc. 320484 Rev. C 11/14. All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

Contact us today!

Call **800-533-9655** to speak with a Graco representative, or visit **www.graco.com** for more information.

